WHAM

NEWS, VIEWS, and REVIEWS

Official Publication of the
Wichita Historical Aircraft Modelers, SAM 56, and
the Kansas Sunflower Squadron, FAC Squadron #23

Sunflower Squadron
Wichita, KS

Issue JE2-26
September, 2025

Observations on Propellers for Outdoor Rubber Powered Models — Steve Griebling

The great search for the perfect propeller continues, but I have made a few observations that might be of some value to fellow gum band stretchers'.

1. The higher the pitch and the greater the width of the prop, the lower the rpm. - but --- 2. High drag, slow flying models require lower pitched props than fast, low drag models. (Prop pitch can be compared to the gear ratios of a transmission. If you are going slow, you must be in low gear = low pitch.)

3. Most plastic props do not have true helical pitch. (So what??) I don't know about this either, but many modelers feel that props should have helical pitch.

4. Helical pitch means that at any point along the blades the prop will theoretically pull the airplane forward the same distance for each revolution. Stated another way, the prop will have the same pitch in inches at any point along the blade. Sounds good doesn't it??

5. Pitch in inches can be calculated by multiplying the tangent of the blade angle by the circumference (diameter x pi) at the same point on the blade.
For example: a 7' diameter prop has a tip circumference of 22'. If its tip angle is 20 degrees; Tan 20 = .364; so .364 x 220= 8*. So its pitch is 8' at the tip.

6. The diameter on the blade where the blade angle is 45 degrees is always pitch divided by pi. For example: at 8' pitch; 8/3.1416 = 2.57' = diameter at the 45 degree point.

7. Most bottle formed props never have a blade angle as high as 45 degrees even at the root because R is difficult to twist the blades enough to get a difference in angle of 46" to 220.

8. Under-cambered blades will create a low tip pitch 9 the trailing edge sweeps forward at the tip. This is often responsible for the lack of helical pitch (by calculation) when measuring tip angle of a finished prop. I usually calculate prop blanks to get helical pitch, then mess ft up by slanting the tips forward to eliminate tip stall!

9. Plastic props range in aspect ratio from 2.8 to 4.3, averaging about 3.3. (blade length / blade width). A very low aspect ratio results in a wide blade, but a wide blade with undercamber results in a very great pitch difference from leading to trailing edge and soaks up a lot of power and makes for an inefficient prop.

10. Props for very light weight indoor models are intentionally made very inefficient to keep the RPMs low, but the models are so light that they fly anyway. (Many indoor models have motor weights equal to the airframe weight!) From an old Cleveland Freeflight NL

August 12, 2025 Meeting Minutes

ATTENDEES:
Jeff Englert, Regina & Marty Kline, Linda & Chuck Powell, Ed Salguero, Marilyn & Bill Schmidt, Dave Wiebe

President Powell called the meeting to order; Minutes were approved as delivered.

Treasurer's report reported a positive balance.

OLD BUSINESS:

Reviewed contests.

NEW BUSINESS:


Discussed the upcoming NATS


Tulsa Glue Dobbers Sept 12-13 at Marion!

SHOW AND TELL:

Chuck Powell showed his finished Taylorcraft. Bill Schmidt plan and Brodek kit.

Bill Schmidt showed a 120% size Comet Grumman Avenger TBM.





This is a slick wing dethermalizer set-up developed by Don DeLoach. It releasess the wing off in a straight forward manner. The diagram shows a viscous timer, but a fuse or radio DT could be substituted. The key difference is the use of a straw as a tunnel to run the DT string through the pylon to run the forward lever (rubber band hold).

SAM 56 — Wichita Historical Aircraft Modelers

FLYING ACES — Sunflower Squadron — Wichita, KS

The next SAM 56 Dinner Meeting will be at:

Mediterranean Grill

335 S Towne East Mall Dr., Wichita, KS 67207
(316) 651-5599

Saturday, October 11, 2025

Social Hour @ 6:00 PM, Dinner @ 6:30 PM...

Upcoming events:

Membership Information:

Open to all interested AMA members, founded to encourage and promote model airplane building.

Member dues $20 annually, Subscription only; $12 annually, $18 foreign

LE FIKE - E

Une véritable BÊTE À VOLER

traité pour le vol libre extérieur
par E.FILLON Aéromodéliste
d'après un 3 vues de Nick Decarlis dans le bulletin des Flightmasters aux USA

The French Arachide

Couleur Jaune : flèche et immatriculation en noir . peindre l'intérieur de la cabine avant recouvrement

EXPERIMENTAL N1408Z

Centrage

Poids 125 gr sans moteur

Caoutchouc une boucle de 3x1 long 500 Remontage 1000 tours

4° de piqueur par rapport à la corde de l'aile et 1° à droite

Volets réglables

Dent de loup d'entrainement

Axe cap 8/10

Bambou ϕ 0,5

Butée graphite ou téflon

Ressort

Souplisseau ou gaine thermofit

Butée arrêt

cap 6/10

Rondelle Soudé

3 Rondelles Libres

Gousets Balsa 10/10

Bloc et plaques Styrofoam ou Balsa leger

Cylindres factices

Gouvernail réglable

Position à l'échelle

Paille ϕ 1,5

Balsa moyen 3x1

Papier bristol

Coller en place le train après finition fuselage

Recouvert Japon

Roue ballon Styrofoam ou balsa ϕ 19 à 20

2 Cales balsa 15/10 Suivant intrados nervure

Araldite

cap 3/10

Balsa 3x3 profilé

3 pailles ϕ 1,5 collées à l'intérieur

Mats paille ϕ 1

Alu

Contour à l'échelle

Balsa 0,8x1,5

Balsa 1,5x1,5 coupé courbe

Alu 3/10

Balsa 1,5x1,5

Bambou ϕ 0,5 cintré à chaud

Coller de fuselage après recouvrement

le stabilo papier pré tendu l'alcool tension

recouvrement et dérive en Japon fin sur cadre à et enduit de Trés dilué

Balsa 1x1,5

à l'extrados 1x1

Gabarits hélice Balsa ϕ 160

ou hélice plastique du commerce

Attention tension alcool

Aile fragile et enduit

très sujette très dilué

à déformations sécher longuement sur forme

Balsa 1x1,5

Flasque avant cp 10/10

Bloc Balsa moyen ep 10

Aile gauche vrillée +3° en bout

Contour aileron

2 Balsa moyen 1,5

Renfort

Balsa 1x1

Balsa 1,5x5

Gousets balsa 5/10

Entailler pour donner le dièdre et coller Araldite

Dièdre

Nota : original né en bout d'aile

8 mm l'avion Fike pas de dièdre

Le STINSON

SENIOR TRAINER Modèle * C

AVION ECOLE US 1935

Maquette Volante taille "PEANUT"
par E Fillon Aeromodéliste

The French Arachide

X-13817

Envergure 13" . 330

Centrage

Couleurs possibles crème et bleu foncé Bleu et orange

Documents : MAN . MRA
The Stinsons A pictorial History by Jim Underwood

Souplisseau ou gaine thermofit
Cap 6/10 .020"
Rondelle teflon
Palier plastic
Rondelles laiton
Doigt cap 3/10 .016" Soudé

roue ϕ 5.20"

Recouvrement total papier Japon leger bleu ou crème (à défaut) jaune

Moteur caoutchouc une boucle de 300 poids 2 à 3,5 gr

Roues ϕ 16 .630"

Dièdre

bambou ϕ 5/10 .020" fils nylon

bambou 5/10 x2 .020" x .080"

balsa 1,5x1,5 .060" sq

balsa 1 .040"

bloc balsa tendre

balsa 6/10 .024"

bois dur

PVC

balsa 6/10 .024"

balsa 1 x 2 .040" x .080" profilé

Laiton ou Alu 3/10 .012"

bambou ϕ 1 .060"

bambou

toutes les baguettes balsa 1x1 .040 sq

Mâts bambou ϕ 5/10

balsa tournée

Recouvrements balsa 4/10 1/64" sur faux couples ou blocs Styrofoam évidés

Hélice en balsa ou plastic ϕ 120 à 140

Carénages en balsa leger ou Styrofoam

broche tube plastic ϕ 1x2 et 2x3 ou Alu

bord d'attaque balsa 2x2 5/64 sq profilé

balsa 1 x 2 .040" x .080"

bord de fuite balsa 1 x 3 .040" x .120"

profilé

Contours des ailerons

balsa 6/10 .024"


Balsa 1,2 .048"

Contours bambou ϕ 5/10 1/32" cintré à chaud

Acétate 2/10 .008"

Balsa 6/10 .024"

Echelle 1/4,75



L.G. Braces
1/16" x 1/8" Balsa


Dihedral Braces
1/32" Bass

1/16" sq. Sliced Rib--
Airfoil: Sprungbatten 3406

Wing L.E. & T.E.
1/16" Balsa
Dihedral 1-1/4" per side


Tips
2 laminations
1/64" x 1/32" Bass

Stab
2 Laminations
1/64" x 1/32" Bass




1/32" sq. Balsa






Motor Tube--.020" balsa around .25" dia. mandrel
.020" M.W. ends silked and bound in the
usual fashion--glue to nose plate and rear gusset
at the odd angle shown.
I used a plastic prop from one of those indoor Czech 'Flies;
easy to replace. 3 deg. down, 3 deg. right thrust.

Fin-- 2 Laminations
1/64" x 1/32" Bass
Glue fin on and cover
after mounting stab



All fuselage framing 1/16" sq. and
sheet balsa; sheet cockpit area,
above and below wing, and
nose to rear of cowl.



Wheel Pants:
Cut outline from .020" bass
with grain running as shown.
Glue braces (1) & (2) down
& piece up (3) then cut away
the middle material.

My Plane is green on yellow Esaki
per Professor Fate's comments in Sept/Oct 99 FAC News;
lettering, cheat line, and registration numbers black.
Wire and brace points are shown on the drawing;
the plane flies well without them. However, as this
model is meant to raise smiles more than to battle
Mr. Smoothie, it might be fun to include them.
A small twig of a panic brace, running from
the fuse to the right wing T.E., was necessary
to control flopping about.

Cowl and mechanical details
1/64" bass, horiz. grain, tissue covered,
glued to nose plate with a strip of black
condenser paper (my NoCal equivalent
of FAC-requisite dummy radial engine)

NoCal JeeBee Mod. E

Des. & Dr. Michael J. Heinrich
After Bob Hirsch & Rocky Russo
Thanx to Flying Aces

12/99MJH

HAWKER SIDDELEY HARRIER

Designed By P.A.Shepherd

